



PRODUCT INFORMATION

FARMER

F55 F55A F65



3 GREAT PARTNERS

TOUGH ENOUGH TO SATISFY PROFESSIONALS, BUT ESPECIALLY BUILT FOR FARMERS, RANCHERS, COMMERCIAL TREE COMPANIES AND CASUAL USERS READY TO "STEP UP" FROM THE "MINI" TYPE SAWS.

When Partner introduced the first FARMER saw, model F55, it proved to be one of the best industry values and became the most popular selling saw in our line. Today, there are THREE models in the FARMER series, enabling you to choose the one best suited to your particular needs. One thing is sure, however, any FARMER model you select will deliver the top performance you expect from a PARTNER chain saw—we build them tough!

FARMER F55 F55A F65

STANDARD FEATURES ON ALL FARMER MODELS

THE ENGINE OF THE PARTNER FARMER

is of Partner design and consists of a two-stroke, loop-scavenged unit. The engine is lubricated by adding 4% oil to the gasoline. The cylinder is hard-chromed with an oil-binding surface to ensure good lubrication and a long life. The crankshaft and connecting rod are made of chrome-nickel steel and carried in ball and roller bearings.

CARBURATOR

Of diaphragm type with automatic fuel pump and permits operation in all positions.

PARTNER IGNITRON IGNITION

Farmer is fitted with the Partner Ignitron system which has eliminated the need for contact breaker points. The entire system is completely insensitive to moisture and impurities. This new and advanced ignition system has a fixed firing point, which ensures that ignition always occurs at exactly the right moment.

CLUTCH

Automatic-operation unit of centrifugal type so that the chain is engaged and disengaged at an engine speed of 3,200 r.p.m., thus preventing the engine from stalling should the tree be felled "pinch".

OIL PUMP — TANK

Automatic chain lubrication by means of a high-pressure oil pump incorporated in the oil tank. The oil tank is built into the crankcase so that the oil is preheated by the engine, this being important for chain lubrication—particularly during the winter. The oil tank has a capacity of one pint.

FUEL TANK

Capacity one quart. The tank has a suction hose with a fuel filter and a robust air-venting valve. This means that the saw can be operated to the last drop of fuel, no matter whether the saw is in the lopping or the felling position.

AIR FILTER

Easily removable, can be dismantled for cleaning.

COUNTERHOLD

Suitable for lopping and designed so that flow of sawdust does not trouble operator.

REAR HANDLE

Designed as pistol grip with all controls grouped for one-hand operation—an important safety factor.

THROTTLE CONTROL

Conveniently located as trigger in pistol grip. Automatic return to idling position when pressure on it is released.

CHAIN

3/8" pitch. Chain speed at 8,500 r.p.m. is 58 feet per second.

SPECIAL FEATURES

Farmer F55


Capacity 3.4 cu. in.
Weight with 15" bar and chain..... 15 lbs

Farmer F55A

Capacity 3.4 cu. in.
Anti-vibration handles
Interlock key
Weight with 15" bar and chain..... 15 lbs

Farmer F65

Capacity 4.0 cu. in.
Anti-vibration handles
Interlock key
Weight with 15" bar and chain..... 16.3 lbs



**Partner Industries
of America, Inc.**

1025 Lambrecht Rd., Frankfort, Illinois 60423
Telephone (815) 469-3911 TELEX 723 445