



357 XP®

The Husqvarna 357 XP® is among our latest generation of professional saws. It's the perfect all-around saw for everything from felling, to limbing and to cross-cutting. High power and rapid acceleration in combination with superior ergonomics, low vibration levels and a slim body ensure both effectiveness and less effort. A lightweight, effective and reliable saw for demanding professional applications.



MAGNESIUM CRANKCASE
Sturdily built crankcase withstands high rpms and tough professional use, ensuring a long service life.



AIR INJECTION
Centrifugal air cleaning system removes larger dust and debris particles before reaching the air filter. This results in reduced air filter cleanings and improved engine life.



THREE-PIECE CRANKSHAFT
Forged three-piece crankshaft for maximum durability for the toughest applications.



FRONT HANDLE ERGONOMICS
Better grip and a 7° offset handle reduces fatigue.

Features

- LowVib® sparing the user's arms and hands
- Adjustable chain oil pump
- Quick-release air filter
- Intuitive, combined choke/stop control
- Quick and easy chain adjustment
- Easy to maintain with snap locked cylinder cover
- Smart Start® for easy starting
- Increased safety, inertia activated chain brake

Technical data

Cylinder displacement	56.5 cc
Power output	4.4 hp
Idling speed	2700 rpm
Maximum power speed	9600 rpm
Maximum recommended engine speed	14000 rpm
Cylinder bore	1.81 inch
Cylinder stroke	1.34 inch
Ignition system	SEMAM50
Ignition module air gap	0.01 "
Spark plug	Champion RCJ7Y, NGK BPMR7A
Electrode gap	0.02 "
Carburetor model name	HDA174
Fuel tank volume	1.44 US pint
Oil tank volume	0.8 US pint
Oil pump type	Adjustable flow
Oil pump capacity	5-15 ml/min
Chain pitch	.325" / 3/8"
Recommended bar length, min-max	13"-20"
Chain speed at max power	70.21 fts
Bar mount	Small
Equivalent vibration level (ahv, eq) front / rear handle	3.9/4.2 m/s ²
Sound pressure level at operators ear	101 dB(A)
Sound power level, guaranteed (LWA)	114 dB(A)
Weight (excl. cutting equipment)	12.1 lbs

ARTICLES		
965 55 04-74	18" Bar, .3/8" Pitch, .050" Gauge	\$ 719.95
965 55 04-73	18" Bar, .3/8" Pitch, .058" Gauge	\$ 719.95
965 55 04-76	20" Bar, .3/8" Pitch, .050" Gauge	\$ 729.95
965 55 04-75	20" Bar, .3/8" Pitch, .058" Gauge	\$ 729.95
965 60 83-01	24" Bar, .3/8" Pitch, .050" Gauge	\$ 739.95

