



359

Husqvarna 359, the robust mid-range professional saw for various use. With raw strength in a wide range of speeds, with a slim and easy to handle body and low vibration levels, the 359 is a truly versatile saw for the widest variety of tasks. A reliable and effective tool for the most demanding professional needs.



QUICK-RELEASE AIR FILTER
Facilitates cleaning and replacement of the air filter.



COMBINED CHOKE/STOP CONTROL
Allows for easier starting and reduces the risk of engine flooding.



SNAP-LOCK CYLINDER COVER
Saves time when changing spark plugs and cleaning.



SMART START®
The engine and starter have been designed so the machine starts quickly with minimum effort.

Features

- Increased safety, inertia activated chain brake
- Less filter cleanings with Air Injection
- Magnesium crankcase designed for professional use
- Maximum durability for tough applications
- LowVib® sparing the user's arms and hands
- Adjustable chain oil pump
- Quick and easy chain adjustment
- Ergonomic grip with angled front handle

TECHNICAL DATA	
Cylinder displacement	59 cc
Power output	3.9 hp
Idling speed	2700 rpm
Maximum power speed	9000 rpm
Cylinder bore	1.85 inch
Cylinder stroke	1.34 inch
Ignition system	SEMAM50
Ignition module air gap	0.01 "
Spark plug	NGK BPMR7A
Electrode gap	0.02 "
Carburetor model name	HDA174
Fuel tank volume	1.44 US pint
Oil tank volume	0.8 US pint
Oil pump type	Adjustable flow
Oil pump capacity	5-15 ml/min
Chain pitch	.325" / 3/8"
Recommended bar length, min-max	13"-20"
Chain speed at max power	70.21 fts
Equivalent vibration level (ahv, eq) front / rear handle	3.9/4.2 m/s ²
Sound pressure level at operators ear	101 dB(A)
Guaranteed sound power level, LWA	114 dB(A)
CE certified	No
Weight (excl. cutting equipment)	12.1 lbs

ARTICLES		
967 04 17-22	16" Bar, 3/8" Pitch, .050" Gauge, Assembly Required	\$ 539.95
967 04 17-06	16" Bar, 3/8" Pitch, .058" Gauge, Assembly Required	\$ 539.95

